

## PET MATTE SILVER POLYESTER 2375

### Face Material

Matte Silver Polyester

Type	Polyethylene Terephthalate
Colour and Finish	Matte silver
Weight	70 g/m <sup>2</sup> ±5%
Thickness	75 μm ± 5%

### Adhesive

Type	Acrylic UV-based
Quantify	36 g/m <sup>2</sup> ±2%

### Liner

Type	60gsm white glassline
Colour	White
Weight	60 g/m <sup>2</sup> ±5%
Thickness	50 μ ±5%

### Physical properties

180° Peel force	≥ 21.096 (GB/T2792-98) N/cm
Initial tack	≥ 7 (GB/T4852-94) Steel ball
Retaining force displacement	≤ 24 (GB/T4851-98) mm
Minimum labelling temperature	10 °C
Application temperature	-10~80 °C
Adhesion	Good
Store condition	Keep indoor, airiness, avoiding high humidity and direct sunlight, can keep one year in room temperature & humidity.
Printing method	Offset, letterpress, flexo, screen printing, bronzing, gravure printing
Die-cutting property	Good
Size and Roll	1080 mm x 1000 m or any other length can be cut
Recommended application	Food labels, healthy products, electronic labels, etc.

### Statement

- Attached technical data for reference only, not for product quality assurance.
- Please complete related tests before application to avoid any unknown risks
- Regarding to product guarantee, please refer to general trade terms, except any other terms in new laws.



**UNIMARK**

Кабельные и портативные принтеры  
Термотрансферные принтеры

Маркировка кабеля и провода  
Сканеры штрих-кода, ТДС

Этикетки для термотрансферной и лазерной печати